

MCWX2GD SUSPENDED CRANE SCALES



MCWX2GD crane scales for use in areas classified as hazardous

Industrial crane scales for use in areas classified as hazardous (Zone 1 and 21, 2 and 22) in accordance with Ex II 2GD IIC T4 T197°C X protection.

Structure completely in stainless steel, with IP68 protection degree. **LITTLE SPACE IS TAKEN UP** allowing the best use of the lifting devices. Predisposed for an upper connection ring and lower hook.

MAIN FEATURES

- Indicator with 17-key numeric-functional waterproof keyboard.
- LCD display with 6 25-mm high contrast digits and icons for showing the active functions.
- Precision: +/- 0.1% F.S.
- Built extremely sturdy in IP68 stainless steel.
- Fitted with upper and lower shackle GR3 (GR6 for the 6T version).
- Digital set-up and calibration programmable directly from keyboard using a sample weight.
- Operating temperature: -10 /+40 °C.
- Adjustable digital filter, anti vibration and oscillation.
- Programmable auto switch-off power for energy saving.
- Hermetically sealed extractable rechargeable battery, with 160-hour operating time; rechargeable in safe area.
- Equipped with 230Vac 50 Hz battery charger to be used in safe area.

OPTIONS AND ACCESSORIES

- Additional rechargeable battery pack, for use the crane scale 24/7.
- Swivelling bottom hook.
- Connection ring.
- ACCREDIA calibration certificate according to OIML/ASTM standards.

KEYBOARD FUNCTIONS

- Zeroing.
- Automatic Tare.
- Presetable Tare.
- Tare database (up to 10).
- ID1 and ID2 10-digit Codes.
- Selectable function command.
- On/off switching.

SELECTABLE FUNCTIONS

- **Simple display and/or with sensitivity HR x 10.**
- **Net/Gross.**
- **lb/kg conversion.**
- **Weights accumulation** (with up to 10 storage values).
- **Formula weighing.**
- **Counting** with function of entering the known A.P.W.
- **Hold.**