

## JB4

# "JB4": JUNCTION BOX WITH OVERVOLTAGE PROTECTION, UP TO 4 LOAD CELLS



Simple junction box with IP67 protection and 4 inputs equipped with electronic board for junction of the signals of 2, 3 or 4 load cells. Screw terminal boards to facilitate the connection. The protection circuit protects against lightning and overvoltage. The reduced costs make it the ideal choice for static weighing systems such as silos, tanks and big containers.

#### Working in cooperation with:

#### POSITIVE WEIGHING SOLUTIONS LTD

UNIT 8 CLIFTON CENTRE, SPRING LANE SOUTH - WR14 1BJ - MALVERN Tel. 01684 561002 lucy@positiveweighing.co.uk The best solution for advanced industrial applications

### **TECHNICAL FEATURES**

- Case in ABS. Protection degree: IP67 protection degree
- Protection degree IP68 with the use of GELBOX anti condensation gel.
- Maximum input voltage: 5Vdc.
- Maximum input current: 700mA.
- Peak pulse current: 15kA.
- Maximum input load cell signal: 1000mV.
- Temperature effect: 50ppm/°C.
- Dimensions (lxwxh): 120x80x55mm.





DINI ARGEO FRANCE sarl France DINI ARGEO GMBH Germany DINI ARGEO UK Ltd United Kingdom DINI ARGEO WEIGHING INSTRUMENTS Ltd China DINI ARGEO OCEANIA Australia



COMPANY HEADQUARTERS Via Della Fisica, 20 41042 Spezzano di Fiorano Modena - Italy Tel. +39.0536 843418

#### **POSITIVE WEIGHING SOLUTIONS LTD**

.....

UNIT 8 CLIFTON CENTRE, SPRING LANE SOUTH - WR14 1BJ - MALVERN

Tel. 01684 561002 lucy@positiveweighing.co.uk

SALES AND TECHNICAL ASSISTANCE SERVICE

All the specifications and images can be subject to variations and upgrades without prior notice.