

MULTIFUNCTION WEIGHT INDICATORS "DFW XP"



SELECTABLE FUNCTION MODES

- The user can select the operating modes directly using the dedicated key*:
 - High resolution display x 10
 - Precision weighing with temporary recalibration via a sample weight (for internal factory use)
 - Net/Gross
 - Lb to Kg converter
 - Free conversion factor (for meter and litre counters etc.)
 - Weight totalizer
 - Formulizer
 - +/- controller with quick target and threshold input
 - Percentage weighing
 - Percentage batching with programmable target
 - Piece counter
 - Hold
 - Two-speed filling/batching with reset upon starting (with optional DFIO)

The "alibi memory" and "setpoint" functions are available in combination with the required operating mode and they are activated automatically when installing the relevant optional board.

New version of DFWXP weight indicators with completely renewed weighing program and keyboard. The wide range of operating modes and the available interfaces make it perfect for many industrial and commercial weighing applications. It can be used as scales and platforms on the ground, mobile scales etc. Type-approved CE-M(OIML R-76/EN45501).

MAIN FEATURES

- 5-key functional or 17-key numerical and functional waterproof keypad, with indication for quick access to main functions and regulations.
- 25mm LCD backlit display with 6 high contrast digits with icons indicating the active functions.
- Easy to clean **ABS waterproof IP65** enclosure; resistant to harsh and corrosive environments (IP40 on version with thermal printer).
- Dimensions in mm: 278x125x186 mm
- Suitable for use on the table, column, or wall.
- The "...XP..." versions are provided with attached thermal printer and real time clock.
- 24-bit A/D converter, 4 channels, up to 200 conv./sec. and up to 8 signal linearisation points
- Up to 10.000e or multirange 3 x 3000e @ 0,3 μ V/e in CE-M approved versions for legal for trade use.
- Up to 1.000.000 displayable divisions with internal resolution up to 3.000.000 points
- Digital calibration and set-up through keyboard or PC with DINITOOLS.
- Built-in rechargeable battery (60 hours with one 350-Ohm load cell) and 110-240 Vac internal power adapter
- Connectable with up to 8 350-Ohm load cells or up to 16 700-Ohm load cells.

I/O SECTION

- RS232/C port configurable for connection with printer/labeller, or for attached printer.
- RS232/C (or optionally **RS485**) bi-directional port configurable for PC, PLC, remote display, and radio modem. Quick RJ RS232 plug connection.
- IR input only available for models with simplified 5-key keypad.

KEYBOARD FUNCTIONS

- Zeroing, Automatic tare, Presettable tare, printing and/or data transmission, selectable function command, on/off switching, backlit setting, function mode quick selection, user menu.

- Optional functions:
 - PEAK, detection of weight peaks (code DFWPK)
 - Newton to Kg converter (code DFWPK)
 - Input-output (on request).
- Access to the user menu is gained using the dedicated key* to adjust the weighing filter, date and time, setpoint and tare weight, which the user can access by entering a programmable access password.

* These quick access keys to the menus can be blocked by configuring a dedicated password.

AVAILABLE FUNCTIONS FROM REMOTE CONTROL

- **Optional radiofrequency 6-key remote control:** zero, tare, enable / disable function, print, switch-off.
- **Optional infrared 19-key remote control:** zero, tare / manual tare, enable / disable function, print, switch-off (IR input only available for models with simplified 5-key keypad).

MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- Australian legal for trade certificate of approval (NMI S788)

17-key Version: Database of 20 tares, 2 Numeric IDs, keyboard lock, repetition of last printout made, quick target insertion, APW, threshold and setpoint.

MASTER/REPEATER OPTION

- Specific program (**MSTSLV** code) for use of the indicator as a universal weight repeater or as a multi-scale repeater (**MASTER**) in combination with DFV/DGT/MCW.

FUNCTIONING MODES:





- **Multi-scale repeater (MASTER):** function which allows to repeat up to 32 independent scales, with the possibility of managing their functions, or displaying and printing the sum of the weights of all the scales.
- **UNIVERSAL weight repeater:** function which allows to repeat the weight of any scales, through the configuration of the input string.

LANGUAGES AVAILABLE FOR PRINTING

- IT, EN, FR, DE, ES, PT, CN*, EL*

* For Chinese and Greek a programming of the printer/labeler is required (S1, only at the time of order)

Available versions

	Code	Description
	DFWXP	5-key indicator. IP65 ABS case, backlit LCD display.
	DFWKXP	17-key indicator. IP65 ABS case, backlit LCD display, and standard weighing programme.
	DFWPXP	5-key indicator with attached printer and real time clock. ABS case, backlit LCD display.
	DFWKXP	17-key indicator with attached printer and real time clock. ABS case, backlit LCD display.